



RELIABLY SEALED!

CLOUTH®-SEAL sealing strips – optimum sheet guidance on the drying cylinder

RELIABLY SEALED!

Reliable sheet guidance thanks to specially designed silicone sealing strips

- Safe for dryer fabrics
- Increased efficiency and lower energy consumption
- Improved process reliability
- Maintenance-friendly and economical
- Easy installation and removal

CLOUTH®-SEAL – RELIABLE SHEET GUIDANCE THANKS TO SPECIALLY DESIGNED SILICONE SEALING STRIPS



At the moment the sheet is released from the drying cylinder, it is exposed to particular stresses. The result can often be web breaks and unplanned, costly machine downtimes.

With the help of technical air installations, which are ideally equipped with CLOUTH®-SEAL sealing strips, a targeted vacuum is generated and the sheet is supported at this critical moment.

CLOUTH®-SEAL provides more process reliability, maximum system availability and increased machine efficiency.

Joh. Clouth GmbH
Johann-Clouth-Straße 1 – 5
42499 Hückeswagen
Germany

Tel. +49 2192 853-0
Fax +49 2192 853-333

sales@clouth-group.com
www.clouth-group.com


[07/2023]

Advantages of the CLOUTH®-SEAL silicone sealing strips

- **No damage to the dryer fabrics:**
Non-abrasive and slippery silicone protects the dryer fabrics.
- **Increased efficiency and lower energy consumption:** The highly flexible silicone has excellent sealing properties, increasing machine efficiency and reducing energy consumption.
- **More process reliability:**
Stress reduction, lower edge flutter and reduced sheet breaks ensure better-running systems.
- **Maintenance-friendly and resource-saving:**
Durable long-life material reduces sheet breaks, downtime and waste.
- **Easy to install and remove:**
The simple installation can be optimised by the use of our CLOUTH DOCTOR CLEAN® systems. The slippery silicone ensures smooth removal.

Standard design:

- Thickness mm (inch): 2.0 (0.08)
- Width mm (inch): 51 (2)
- Heat resistance: Up to max. 200°C
- Design: End-to-end, individual length, blunted tip



← CLOUTH®-SEAL BT
Standard application
Hardness: 90° +/-5 SHORE A

CLOUTH®-SEAL DG →
Standard application
with dirt protection
Hardness: 90° +/-5 SHORE A



← CLOUTH®-SEAL WDS
Standard application with
increased hot steam resistance
Hardness: 70° +/-5 SHORE A

CLOUTH®-SEAL CF →
Standard application
with increased heat resistance
Hardness: 90° +/-5 SHORE A

